

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product identifier

**Product Name** Klea™ 125

Hazardous Ingredient(s) / Substance identity	REACH Registration No.
Pentafluoroethane (HFC 125)	01-2119485636-25-0005

Use Subject to Member State regulations, applicable uses are: refrigerant

Manufacturer Mexichem UK Limited  
The Heath Business & Technical Park  
Runcorn  
Cheshire  
WA7 4QX  
United Kingdom  
Tel: +44(0) 1928 518880  
E-Mail: info@mexichem.com

Emergency Phone No. IN AN EMERGENCY DIAL 999 (UK Only)  
For specialist advice in an emergency telephone +44(0) 1928 572000

### 2. HAZARDS IDENTIFICATION

Low acute toxicity. High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.  
Liquid splashes or spray may cause freeze burns to skin and eyes.

#### Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) Gases under pressure - Liquefied gas

#### Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Hazard Pictogram(s)



GHS04

Signal Word(s) Warning

Hazard Statement(s) H280: Contains gas under pressure; may explode if heated.

Precautionary Statement(s) P410+P403: Protect from sunlight. Store in a well-ventilated place.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Alternative names Pentafluoroethane (HFC 125)  
R 125

## SAFETY DATA SHEET

### HAZARDOUS INGREDIENT(S)

Hazardous Ingredient(s)	%(w/w)	CAS No.	EC No.	Hazard symbol(s) and hazard statement(s)
Pentafluoroethane (HFC 125)	100	000354-33-6	206-557-8	GHS04; H280

## 4. FIRST AID MEASURES



The first aid advice given for skin contact, eye contact, and ingestion is applicable following exposures to the liquid or spray. See also section 11.

### Description of first aid measures

Inhalation	Remove patient from exposure, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In the event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention.
Skin Contact	Thaw affected areas with water. Remove contaminated clothing. Caution: clothing may adhere to the skin in the case of freeze burns. After contact with skin, wash immediately with plenty of warm water. If irritation or blistering occur obtain medical attention.
Eye Contact	Immediately irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes. Obtain immediate medical attention.
Ingestion	Unlikely route of exposure. Do not induce vomiting. Provided the patient is conscious, wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain immediate medical attention.
Further Medical Treatment	Symptomatic treatment and supportive therapy as indicated. Adrenaline and similar sympathomimetic drugs should be avoided following exposure as cardiac arrhythmia may result with possible subsequent cardiac arrest.
Most important symptoms and effects, both acute and delayed	High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.
Indication of any immediate medical attention and special treatment needed	Remove patient from exposure, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In the event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention.

## 5. FIREFIGHTING MEASURES

General	Non-flammable. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.
Extinguishing media	As appropriate for surrounding fire. Keep fire exposed containers cool by spraying with water.
Special hazards arising from the substance or mixture	Thermal decomposition will evolve very toxic and corrosive vapours. (hydrogen fluoride) Containers may burst if overheated.
Advice for firefighters	A self contained breathing apparatus and full protective clothing must be worn in fire conditions. See Also Section 8

## SAFETY DATA SHEET

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Ensure suitable personal protection (including respiratory protection) during removal of spillages. See Also Section 8
Environmental precautions	Prevent liquid from entering drains, sewers, basements and workpits since the vapour may create a suffocating atmosphere.
Methods and materials for containment and cleaning up	Provided it is safe to do so, isolate the source of the leak. Allow small spillages to evaporate provided there is adequate ventilation. Large spillages: Ventilate area. Contain spillages with sand, earth or any suitable adsorbent material. Prevent liquid from entering drains, sewers, basements and workpits since the vapour may create a suffocating atmosphere.
Reference to other sections	8, 13

### 7. HANDLING AND STORAGE

Precautions for safe handling	<p>Avoid inhalation of high concentrations of vapours. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Atmospheric concentrations well below the occupational exposure limit can be achieved by good occupational hygiene practice.</p> <p>The vapour is heavier than air, high concentrations may be produced at low levels where general ventilation is poor, in such cases provide adequate ventilation or wear suitable respiratory protective equipment with positive air supply.</p> <p>Avoid contact with naked flames and hot surfaces as corrosive and very toxic decomposition products can be formed.</p> <p>Avoid contact between the liquid and skin and eyes.</p> <p>Avoid venting to atmosphere.</p> <p>The fluorinated greenhouse gas R 125 may be supplied in returnable containers (drums/cylinders). The container contains fluorinated greenhouse gases covered by the Kyoto Protocol. The fluorinated greenhouse gases in containers may not be vented to the atmosphere. Regulation (EU) No. 517/2014 of the European Parliament and the Council on certain fluorinated greenhouse gases.</p>
Process Hazards	<p>Liquid refrigerant transfers between refrigerant containers and to and from systems can result in static generation. Ensure adequate earthing. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.</p> <p>Care must be taken to mitigate the risk of developing high pressures in systems caused by a temperature rise when liquid is trapped between closed valves or in cases where containers have been overfilled.</p>
Conditions for safe storage, including any incompatibilities	<p>Keep in a well ventilated place away from fire risk and avoid sources of heat such as electric or steam radiators.</p> <p>Avoid storing near to the intake of air conditioning units, boiler units and open drains.</p>
Specific use	Subject to Member State regulations, applicable uses are: refrigerant

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure controls

#### Occupational Exposure Limits

## SAFETY DATA SHEET

Occupational Exposure Limits	CAS No.	LTEL (8 hr TWA ppm)	LTEL 8 hr TWA mg/m <sup>3</sup>	STEL (ppm)	STEL mg/m <sup>3</sup>	Note
Pentafluoroethane (HFC 125)	000354-33-6	1000	-	-	-	COM

Appropriate engineering controls Provide adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit.

Personal protection equipment Wear suitable protective clothing, gloves and eye/face protection.



Respirators  
In cases of insufficient ventilation, where exposure to high concentrations of vapour is possible, suitable respiratory protective equipment with positive air supply should be used.



Eye Protection  
Wear protective eyewear (goggles, face shield, or safety glasses).



Gloves  
Wear thermal insulating gloves when handling liquefied gases.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	liquefied gas
Colour.	colourless
Odour	slight ethereal
Solubility (Water)	insoluble
Solubility (Other)	Soluble in: alcohols , chlorinated solvents
Boiling Point (° C)	-48.25
Melting Point (° C)	-103
Vapour Density (Air=1)	4.3 at normal boiling point
Vapour Pressure (mm Hg)	10340 at 25 ° C
Specific Gravity	1.19 at 25 ° C

## 10. STABILITY AND REACTIVITY

Reactivity	See Section: Possibility of hazardous reactions
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions. Incompatible materials: finely divided metals , magnesium and alloys containing more than 2% magnesium . Can react violently if in contact with alkali metals and alkaline earth metals - sodium , potassium , barium
Conditions to avoid	Avoid high temperatures.
Incompatible materials	finely divided metals , alkali metals ( sodium , potassium ) , alkaline earth metals ( barium , magnesium ) , alloys containing more than 2% magnesium
Hazardous decomposition products	hydrogen fluoride by thermal decomposition and hydrolysis.

## SAFETY DATA SHEET

### 11. TOXICOLOGICAL INFORMATION

Acute toxicity / Ingestion	Highly unlikely - but should this occur freeze burns will result.
Inhalation / Acute toxicity	LC50 (rat) (4 hrs) > 800000 ppm (3928000 mg/m3) High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.
Acute toxicity / Skin Contact	Unlikely to be hazardous by skin absorption.
Skin corrosion/irritation	Liquid splashes or spray may cause freeze burns.
Serious eye damage/irritation	Liquid splashes or spray may cause freeze burns.
Respiratory irritation	Non-irritant
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	An inhalation study in animals has shown that repeated exposures produce no significant effects (50000ppm in rats).
Mutagenicity	No evidence of mutagenic effects.
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.
Reproductive toxicity	Studies in animals have shown that exposures produce no teratogenic effects.
Specific target organ toxicity — single exposure	Not classified.
Specific target organ toxicity — repeated exposure	Not classified.
Aspiration hazard	Not applicable.

### 12. ECOLOGICAL INFORMATION

Toxicity	The product is predicted to have low toxicity to aquatic organisms.
Environmental Fate and Distribution	High tonnage material produced in wholly contained systems. High tonnage material used in open systems. Gas.
Persistence and Degradation	Decomposed slowly in the lower atmosphere (troposphere). Atmospheric lifetime is 29 years. Does not influence photochemical smog (i.e. is not a VOC under the terms of the UNECE agreement). Does not deplete ozone. Has a Global Warming Potential (GWP) of 3500 (relative to a value of 1 for carbon dioxide at 100 years) according to Annex I of Regulation (EU) No. 517/2014 on certain fluorinated greenhouse gases. Values in Annex I are taken from the fourth assessment report (AR4) of the Intergovernmental Panel on Climate Change. United Nations Framework Convention on Climate Change (UNFCCC) reporting GWP is 2800.
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not applicable.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

## SAFETY DATA SHEET

Effect on Effluent Treatment

Discharges of the product will enter the atmosphere and will not result in long term aqueous contamination.

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Best to recover and recycle. If this is not possible, destruction is to be in an approved facility which is equipped to absorb and neutralise acid gases and other toxic processing products.

Regulatory Information

Disposal should be in accordance with local, state or national legislation.

### 14. TRANSPORT INFORMATION

Hazard label(s)



Road/Rail

UN No.

3220

ADR/RID Class

2.2

ADR/RID Proper Shipping Name

PENTAFLUOROETHANE (REFRIGERANT GAS R 125)

SEA

IMDG Class

2.2

Marine Pollutant

Not classified as a Marine Pollutant

AIR

ICAO/IATA Class

2.2

### 15. REGULATORY INFORMATION

#### European Regulations

EC Classification

According to Regulation (EC) No. 1272/2008 (CLP)  
Gases under pressure - Liquefied gas

Special Restrictions:

The fluorinated greenhouse gas R 125 may be supplied in returnable containers (drums/cylinders). The container contains fluorinated greenhouse gases covered by the Kyoto Protocol. The fluorinated greenhouse gases in containers may not be vented to the atmosphere.

Regulation (EU) No. 517/2014 of the European Parliament and the Council on certain fluorinated greenhouse gases.

Directive 2006/40/EC of the European Parliament and the Council relating to emissions from air-conditioning systems in motor vehicles and amending Council Directive 70/156/EC.

### 16. OTHER INFORMATION

This data sheet was prepared in accordance with Regulation (EC) No. 1907/2006.

## SAFETY DATA SHEET

Information in this publication is believed to be accurate and is given in good faith, but it is for the User to satisfy itself of the suitability for its own particular purpose. Accordingly, Mexichem UK Limited gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.

Klea™ is a trademark, the property of Mexichem SAB de C.V.

Mexichem UK Limited is Registered in England No 7088219. Registered Office The Heath Business & Technical Park,

Runcorn, Cheshire WA7 4QX.

© Mexichem UK Limited 2016.

### Glossary

WEL: Workplace Exposure Limit (UK HSE EH40)

COM: The company aims to control exposure in its workplace to this limit

TLV: The company aims to control exposure in its workplace to the ACGIH limit

TLV-C: The company aims to control exposure in its workplace to the ACGIH Ceiling limit

MAK: The company aims to control exposure in its workplace to the German limit

Sk: Can be absorbed through skin

Sen: Capable of causing respiratory sensitisation

Bmgv: Biological monitoring guidance value (UK HSE EH40)

### Hazard Statement(s)

H280: Contains gas under pressure; may explode if heated.

**The following sections contain revisions or new statements:**

**1,2,4,5,6,7,8,10,11,12,13,15**